


SC  
C



## GENERAL DEMOLITION NOTES

---

ALL EQUIPMENT AND FURNISHINGS REMOVED AND NOT SCHEDULED FOR RELOCATION PER ALTERATION NOTES SHALL BE TURNED OVER TO THE OWNER.

WHERE PLUMBING FIXTURES ARE REMOVED, EXISTING PIPING SHALL BE CAPPED OFF AT THE FLOOR WALL SURFACE. REFER TO MECHANICAL DEMOLITION DRAWINGS FOR ADDITIONAL INFORMATION.

WHERE NEW FINISHES ARE INDICATED TO BE PROVIDED BY FINISH SCHEDULE, CONTRACTOR SHALL REMOVE EXISTING FINISHES INCLUDING LIGHT FIXTURES AND ELECTRICAL DEVICES NOT SCHEDULED OR INDICATED TO REMAIN. REFER TO OTHER DRAWINGS, SCHEDULES AND NOTES FOR ADDITIONAL INFORMATION. WHERE EXISTING CERAMIC TILE OCCURS AND IS NOT SCHEDULED TO REMAIN THE CONTRACTOR SHALL REMOVE AND REPAIR OR FILL IN AS REQUIRED TO ACCOMMODATE INSTALLATION OF SCHEDULED FINISHES.

REFER TO MECHANICAL, ELECTRICAL, AND PLUMBING DRAWINGS FOR ADDITIONAL INFORMATION. COORDINATION REQUIRED.

WHERE EXISTING WALL, CEILING OR FLOOR FINISHES ARE TO REMAIN AND ARE DISTURBED BY RENOVATION AND/OR NEW CONSTRUCTION, THEY SHALL BE REPAIRED AS REQUIRED TO MAINTAIN ORIGINAL INTEGRITY OF ADJACENT CONSTRUCTION. REFER TO FINISH SCHEDULE FOR ADDITIONAL INFORMATION.

WHERE NEW CONSTRUCTION OCCURS, CARE SHALL BE TAKEN SO AS NOT TO DISTURB THE INTEGRITY OF EXISTING RATINGS, AND FIRE PROTECTED ELEMENTS UNLESS SPECIFICALLY DESIGNATED TO BE REMOVED.

THE DEMOLITION CONTRACTOR WORK SHALL CONFORM TO ALL LOCAL, STATE AND NATIONAL SAFETY REGULATIONS.

THE DEMOLITION CONTRACTOR SHALL REMOVE, STORE AND SECURE ALL SALVAGED ITEMS AS INDICATED IN THE DEMOLITION NOTES OR AS DIRECTED BY OWNER.

BEFORE STARTING WORK, DEMOLITION CONTRACTOR TO CHECK AND VERIFY DIMENSIONS AND CONDITIONS. SURVEY ALL EXISTING CONDITIONS, PREPARE A LIST OF EXISTING DAMAGED AREAS VERIFIED BY PHOTOGRAPHS AND SIGNED BY CONTRACTOR AND OTHERS CONDUCTING INVESTIGATION.

DEMOLITION CONTRACTOR TO COORDINATE WORK AND ESTABLISH APPROVAL FROM OWNER FOR PROCEDURES, METHODS OF DEMOLITION REGARDING NOISE CONTROL AND THE USE OF BUILDING FACILITIES INCLUDING STAIRS, TOILETS, HEATING, AIR CONDITIONING, ELECTRICITY, ETC. THE EXISTING ELEVATOR MAY BE USED FOR CONSTRUCTION PURPOSES IF APPROVED BY OWNER.

WHERE NEW OPENING IS REQUIRED IN AN EXISTING WALL, NEW LINTELS SHALL BE PROVIDED AS NECESSARY.

WHERE EXISTING TOILET ACCESSORIES OCCUR AT RENOVATED PLUMBING FIXTURE AREAS, THE EXISTING ACCESSORIES SHALL BE RETURNED TO OWNER.