























LIGHTING FIXTURE SCHEDULE						
SYMBOL	TYPE	MOUNTING	WATTAGE & LAMP	SHIELDING	BALLAST	NOTES
	F1	RECESSED 3 3/4"	(1) 28W. "T5" FLUOR. LAMP	BLACK METAL DIFFUSER WITH ROUND HOLES	*PROGRAM START 0.88 BALLAST FACTOR	PROVIDE 3/4" GAP AT ADJACENT FIXTURES FOR CONTINUOUS ROW MOUNTING AS SHOWN ON PLANS.
	F2	RECESSED 6 1/16"	(4) 25W. "T8" FLUOR. LAMPS	CONCAVE ACRYLIC LENS	(2) 2-LAMP 0.88 BALLAST FACTOR & PARALLEL WIRING	3FT. DIA. ROUND TROFFER.
	F3	RECESSED 6 1/16"	(6) 32W. "T8" FLUOR. LAMPS	CONCAVE ACRYLIC LENS	(3) 2-LAMP 0.88 BALLAST FACTOR & PARALLEL WIRING	4FT. DIA. ROUND TROFFER.
	F4	RECESSED 6 3/4"	(2) 17W. OR 32W. "T8" FLUOR. LAMPS/SECTION	FROSTED CLEAR 1/4" ACRYLIC LENS	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 2FT., 4FT., OR 8FT. HOUSING LENGTHS.
	F5	WALL	(2) 32W. "T8" FLUOR. LAMPS	PERFORATED SHIELD	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 4FT. OR 8FT. HOUSING LENGTHS.
	F6	CABLE	(2) 32W. "T8" FLUOR. LAMPS/SECTION	ROUND PERF. WITH ACRYLIC OVERLAY	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 4FT. HOUSING LENGTHS, AS SHOWN ON PLANS.
	F7	RECESSED 11 1/4"	(1) 42W. CFL TRT LAMP	SOFT TITANIUM REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F8	RECESSED 5 1/4"	(3) 32W. "T8" FLUOR. LAMPS	ACRYLIC DIFFUSER	*PROGRAM START 0.88 BALLAST FACTOR & PARALLEL WIRING	
	F8A	RECESSED 5 1/4"	(3) 17W. "T8" FLUOR. LAMPS	ACRYLIC DIFFUSER	*PROGRAM START 0.88 BALLAST FACTOR & PARALLEL WIRING	
	F9	RECESSED 11"	(1) 42W. CFL TRT LAMP	LOW IRIDESCENT REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F10	RECESSED 7 3/4"	(1) 42W. CFL TRT LAMP	LOW IRIDESCENT REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F11	RECESSED 10 3/8"	(1) 42W. CFL TRT LAMP	LOW IRIDESCENT REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F12	RECESSED 5 1/4"	(1) 32W. "T8" FLUOR. LAMPS	EXTRUDED ACRYLIC DIFFUSER	*PROGRAM START 0.88 BALLAST FACTOR & PARALLEL WIRING	
	F14	COVE	(1) 32W. "T8" FLUOR. LAMP	PARABOLIC REFLECTOR	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 4FT. OR 8FT. HOUSING LENGTHS.
	F15	PENDANT	(1) 42W. CFL TRT LAMP	LOW IRIDESCENT REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F16	PENDANT/ STEM	(3) 32W. "T8" FLUOR. LAMPS	WIREGUARD AND UPLIGHT APERTURE	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 4FT. HOUSING LENGTHS.
	F17	RECESSED 5 1/4"	(2) 32W. "T8" FLUOR. LAMPS	REGRESSED ACRYLIC DIFFUSER	*PROGRAM START 0.88 BALLAST FACTOR & PARALLEL WIRING	
	F18	RECESSED 7 7/8"	LED LAMPS	LOW IRIDESCENT REFLECTOR	*PROGRAM START 0.88 BALLAST FACTOR	
	F19	PENDANT	(1) 42W. CFL TRT LAMP	OPAL GLASS SHADE	*PROGRAM START 0.88 BALLAST FACTOR	
	F20	PENDANT	(1) 42. CLF & (1) LED-MR16 DOWNLIGHT	MATTE WHITE ACRYLIC DIFFUSER	*REMOTE BALLAST PROGRAM START 0.88 BALLAST FACTOR	
	F21	WALL	(2) 32W. "T8" FLUOR. LAMPS	WHITE BLADE LOUVER	AS SPECIFIED BY CATALOG NUMBER	*MOUNTED INDIVIDUAL OR IN CONTINUOUS ROWS, 4FT. OR 8FT. HOUSING LENGTHS.
	F?					
		UNIVERSAL	LED LAMP	STENCIL FACE		REFER TO LIGHT FIXTURE SCHEDULE NOTES 7 & 8.